



best in the  
**LongRun**

# Tie Down Mate/ Tie Down Mate Kit

Assembly/Installation Instructions  
Part #86071/86072



**Part 86071** - Kit contains the following components:

#	Qty.	Part #	Description
1	1	48171	Tie Down Mate Anchor
2	1	48172	Installation Rod
3	1	17530	Anchor Shaft Cap
4	1	17531	Drive Rod Cap

**Part 86072** - Kit contains the following components:

#	Qty.	Part #	Description
1	1	48171	Tie Down Mate Anchor
2	1	48172	Installation Rod
3	1	17530	Anchor Shaft Cap
4	1	17531	Drive Rod Cap
5	1	15530	Nylon Carry Bag
6	1	18025	15' Poly Rope
7	1	18040	Float

The Tie Down Mate is designed as a ground anchor to secure your watercraft to a beach area.

1. Choose a location on the beach where you will want to secure your watercraft.
2. Remove the plastic cover from the anchor and lift out the installation rod.
3. Place the installation rod through the small hole in the top of the anchor to form a "T" handle in which to screw the Tie Down Mate into the ground or beach area.
4. Using downward pressure, turn the anchor in a clockwise direction until the "loop" is at ground level, or until anchor is secure.
5. Thread the rope provided or a locking cable through the loop and tie your watercraft or boat to the other end.
6. A float is provided for using the Tie Down Mate in shallow water where a "floating" tie up is desired.

Your Tie Down Mate can be used for many items requiring a ground anchor, boats, watercraft, pets, etc.

Instruction Sheet #15350

**TIE DOWN ENGINEERING • 255 Villanova Drive SW • Atlanta, GA 30336**  
**www.tiedown.com (404) 344-0000 Fax (404) 349-0401**



A711: 051116